IN THE CLAIMS:

1. (Previously amended) A system for locating a mobile unit including: means for transmitting a first signal at a relatively high power; means for transmitting a second signal at a predetermined, relatively low power; means for receiving said first signal;

means for determining a first signal strength of said first signal at said means for receiving said first signal;

means for determining whether said first signal strength exceeds a relatively low threshold level so as to determine whether service may be provided;

means for receiving said second signal;

means for determining a second signal strength of said second received at received at said means for receiving said second signal;

means for determining whether said second signal strength exceeds a relatively high threshold level so as to locate the mobile unit within a known distance of said means for transmitting said second signal.

- 2. (Previously amended) A system according to Claim 1, wherein said relatively high power is at least 0 dBm.
- 3. (Previously amended) A system according to Claim 1, wherein said relatively high power is at least 6 dBm, 13 dBm or 20 dBm.
- 4. (Previously amended) A system according to Claim 1, said relatively low power is no more than 0 dBm.
- 5. (Previously amended) A system according to Claim 1, wherein said relatively low threshold level is no more than -85 dBm.

- 6. (Previously amended) A system according to Claim 1, wherein said relatively high threshold level is no less than -65 dBm.
- 7. (Previously amended) A system according to any Claim 1, wherein said means for transmitting said first and second signals transmit said first and second signals at different times.
- 8. (Previously amended) A system according to Claim 1, which is a wireless local area network.
- 9. (Previously amended) A system according to Claim 8, wherein said means for transmitting said first signal is an access point.
- 10. (Previously amended) A system according to Claim 8, wherein said means for transmitting said second signal is an access point.
- 11. (Previously amended) A system according to Claim 8, wherein said means (4) for receiving said first signal is a mobile unit.
- 12. (Previously amended) A system according to Claim 8, wherein said means (4) for receiving said second signal is a mobile unit.
- 13. (Previously amended) A system according to Claim 8, wherein said means for transmitting said first signal is a mobile unit.
- 14. (Previously amended) A system according to Claim 8, wherein said means (4) for transmitting said second signal is a mobile unit.
- 15. (Previously amended) A system according to Claim 8, wherein said means for receiving said first signal is an access point.

- 16. (Previously amended) A system according to Claim 8, wherein said means for receiving said second signal is an access point.
- 17. (Cancelled)
- 18. (Previously amended) A system for locating a mobile unit including:
 a first transmitter for transmitting a first signal at a relatively high power;
 a second transmitter for transmitting a second signal at a predetermined, relatively low power;
 - a first receiver for receiving said first signal;
- a first detector for determining a first signal strength of said first signal at said first receiver;
- a first controller for determining whether said first signal strength exceeds a relatively low threshold level so as to determine whether service may be provided;
 - a second receiver for receiving said second signal;
- a second detector for determining a second signal strength of said second signal at said second receiver;
- a second controller for determining whether said second signal strength exceeds a relatively high threshold level so as to locate the mobile unit within a known distance of said means for transmitting said second signal.
- 19. (Previously amended) An access point configured for use in the system according to Claim 1.